



## Features

- High quality stainless steel chamber, safe and easy-to-clean.
- Microprocessor controller with LCD display, accurate and reliable.
- Equipped with multiple sets of heaters.
- Equipped with leakage protection.
- Equipped with spare temperature control which ensures the product work normally even the main temp. control failed.
- Adopt temperature selection switch which can select the grade according to the heating speed and operating temperature.
- Convenient operation for air inlet, reasonable air duct structure, good temperature uniformity.
- With window on the door for easy observation.
- Anti-hot handle

## Technical Parameters:

1. Temp. range: RT+10°C -300°C
2. Temp. fluctuation:  $\pm 1^{\circ}\text{C}$
3. Temp. resolution: 0.1°C
4. Temp. uniformity:  $\leq \text{Max. Temp.} \pm 3.5^{\circ}\text{C} \%$
5. Power supply: 220V, 50HZ

## Options:

1. Multi-segment programmable control
2. Built-in printer
3. RS485 interface

## Specifications

Model	Volume(L)	Chamber Size (L×W×H)cm	Power Rating (W)	Shelf	Net/Gross Weight (kg)
LDO-300	43	35×35×35	1300	2	35 / 55
LDO-400	81	45×40×45	2000	2	50 / 80
LDO-500	138	50×50×55	2500	2	75 / 110
LDO-600	252	60×60×70	3500	2	110 / 150