


Features

- Microprocessor controller, can accurately control the temperature and gas in incubator.
- Imported oxygen sensor, high accuracy, easily observe oxygen concentration in the operation room at any time.
- High precision temperature sensors, high accuracy and good stability.
- UV Sterilizer, effectively prevent bacterial contamination.
- Stainless steel cultivation and operation room, transparent impact-resistant glass front window for easy observation.
- Latex gloves, comfortable and easy to use.
- Double inside incubator, can put more petri dishes.
- Equipped with leakage protection.
- With USB interface, can store 6 months of data.



Specifications

Model	LAI-3T
Time for creating anaerobic state in sample chamber	< 5 minutes
Time for creating anaerobic state in operation chamber	< 1 hr
Anaerobic environment maintenance time	> 13 hrs.(when no supply of mixed gas)
Temperature Range	RT+3~60 C
Temperature Stability	< ±0.3 C
Temperature Uniformity	< ±1 C
Display Resolution	0.1 C
Timing Range	1~9999min
Power Rating	600W
Power Supply	AC 220V,50HZ
Net/Gross Weight(kg)	240/320
Interior Chamber Size(W×D×H)cm	30×19×29
Operation Chamber Size (W×D×H)cm	82×66×67
Exterior Size (W×D×H)cm	126×73×138
Package Size(W×D×H)cm	133×87×158