



## Features

- Microprocessor controller, accurately control the temperature and gas in incubator.
  - Equipped with large color touch screen,easy operation
  - With imported oxygen sensor and high precision temperature sensor to ensure accuracy, good stability and high security.
  - Automatic control for gas replacement, can set oxygen percentage.
  - Unique oil bottle type pressure relief design, protects internal positive pressure and prevents air leakage.
  - UV Sterilizer,effectively prevent bacterial contamination.
  - Stainless steel cultivation and operation room,transparent impact-resistant glass front window for easy observation.
  - Latex gloves are comfortable and reliable,easy to use.
  - Operation room is equipped with deoxidization catalyst.
- Unique track design for sample transmit,easy operation
  - Sample transfer: can transfer 40 pcs of 90mm plates at a time.
  - Equipped with leakage protection.
  - With USB interface, can store 6 months of data.

## Specifications

<b>Model</b>	LAI-3T-N
Anaerobic state creating	Automatic
Time for creating anaerobic state in sample chamber	< 10 minutes
Time for creating anaerobic state in operation chamber	< 1.5 hrs
Anaerobic environment maintenance time	> 13 hrs.(when no supply of mixed gas)
Temperature Range	RT+3~60℃
Temperature Stability	< ±0.3℃
Temperature Uniformity	< ±1 ℃
Timing Range	1~9999min
Power Rating	800W
Power Supply	AC 220V,50HZ
Interior Chamber Size(W×D×H)cm	42×30×50
Operation Chamber Size (W×D×H)cm	95×68×75
Exterior Size (W×D×H)cm	151×91×161